Colorstar

→ **LOGO MAT • INDOOR**



WHY CHOOSE THIS MAT?

ColorStar mats feature your custom logo or artwork digitally printed on recycled PET material. Choose from 66 standard color options.

- The top layer of the mat contains **100% recycled PET material**
- Photographic Print Quality
- Incredible **stain resistance**: no cross staining, easy to clean
- Produced within **24 hours**
- Also available as unicolor mat

SPECIFICATIONS

SKU	745; 746; 747
Yarn	100% post-consumer recycled PET fibers, twisted and heat-treated • **Yarn weight:** 900 g/m²
Backing	• **Primary backing:** 100% recycled PET non-woven • **Rubber backing:** 100% nitrile rubber with 34% post industrial recycled content in the polymer • For maximum oil resistance, durability, and performance. • Compression-molded with reinforced borders on all four sides • **Thickness:** 1.5 mm - Also available in 3mm rubber backing
Border	• **Thickness:** 2.5 mm • **Width**: 2 cm
Other properties	• **Pile thickness:** 11 mm • **Total weight:** 2,9 kg/m²
Safety	• **Static control:** ISO 6356 (2012) Determination of the static electrical propensity – walking test: -0.3 kVolts. Satisfies IBM test requirements • **Flammability**: Cfl / s1 according EN 13501-1. Passes BS 4790 (1987) determination of the flammability of textile floor coverings: Low radius of effects of ignition.
Recommended use	Recommended for indoor commercial use at entryways, in lobbies, at front desks or anywhere you want to display your company logo, slogan, artwork, or message to customers/visitors or employees

STANDARD SIZES

60x85	85x300	115x250	150x250
75x85	115x180	115x300	150x300
85x115	115x200	150x200	200x200
85x150	115x240	150x240	200x300

SPECIAL SIZES

Max. size: 200 cm x 550 cm

Size Tolerance: +/- 2%
Weight Tolerance: +/- 5%

COLOURS

C1	C9	C17	C25	C32	C39	C46	C53	C60
C2	C10	C18	C26	C33	C40	C47	C54	C61
C3	C11	C19	C27	C34	C41	C48	C55	C62
C4	C12	C20	C28	C35	C42	C49	C56	C63
C5	C13	C21	C29	C36	C43	C50	C57	C64
C6	C14	C22	C30	C37	C44	C51	C58	C65
C7	C15	C23	C31	C38	C45	C52	C59	C66
C8	C16	C24						

How much plastic bottles do we safe?

60 x 85	→	33
75 x 85	→	41
85 x 115	→	62
85 x 150	→	82
85 x 300	→	164
115 x 180	→	132

115 x 200	→	147
115 x 240	→	176
115 x 250	→	192
115 x 300	→	221
150 x 200	→	192
150 x 240	→	230

150 x 250	→	240
150 x 300	→	288
200 x 200	→	256
200 x 300	→	384

CLEANING INSTRUCTIONS

Colorstar mats can be cleaned in several different ways:

1. They can be commercially laundered (see Laundering Instructions)
2. Vacuumed regularly (daily in high-traffic areas; weekly in lower-traffic applications)
3. Cleaned with an extractor, or hosed off as necessary to remove heavy soil.

Hang to dry. Mats should always be dry before they are placed back in service.

Laundering Instructions

1. Flush, 2-3 Min. on a medium water level with a maximum temperature of 49°C
2. Flush (optional), 2-3 Min. on a medium water level with a maximum temperature of 49°C
3. Break, 2-3 Min. on a high water level with a maximum temperature of 49 °C
4. Rinse, 2 Min. on a high water level with cold temperature
5. Rinse, 2 Min. on a high water level with cold temperature
6. Extract on low speed, 1-2 Min.
7. Shake out with the drum turning, 1 Min.
8. Extract, on a maximum of 250G, 3-5 Min.
9. Dry (optional), 5-10 Min. with a maximum basket temperature of 82 °C
10. Cool down, 5 Min.

Additional recommendations

- For Heavy Soiled Mats, increase the temperature up to max. 60°C.
- Break should not exceed pH of 9,5; use low pH non-ionic detergents.
- Do not overdry mats; Basket-temperature of the dryer should not exceed 82 °C.
- If mats are not dried, the final rinse can be increased to 49 °C. This will reduce moisture retention following extraction.
- Lay mats flat following removal from washer; allow mats to cool before rolling.